

FSC891H Black

Black 2-door display cooler with canopy

Product Features

- Approx. 58% more energy efficient than previous FSC-range
- LED illuminated canopy
- Internal vertical LED light
- Black interior and exterior
- Adjustable shelves
- Ventilated cooling
- Hinged alu-framed glass doors
- Adjustable feet with rollers to rear
- Digital temperature display







Strong handles

Black 2-door display cooler with canopy

The FSC range is with a light canopy. The possibility for customized branding is eye-catching and stimulate impulse sales. The unit keeps beverages cold whilst presenting and promoting the products to their best advantage. It has been updated and now uses in average 58% less energy compared to the previous models from the same range.

This model is with black exterior and interior. The black exterior finish looks great, the black interior makes the content stand out especially with LED lights perfectly illuminating the content. It is ideal for high-end cafes, delis and patisseries.

It comes with 5 adjustable black wire shelves, 2 self-closing hinged glass doors, 2 vertical full length LED lights inside the door frame and a LED light canopy.

Design and Material			
Door No & Type	2 hinged self- closing glass doors		
Tempered glass	Yes		
Door Reversible	No		
Shelves No & Type	5 wire shelves white		
Shelf Color	White		
Shelf Dimensions	794 x 540 mm		
Max load on kg/m² Shelves	196		
Canopy Type	D-Shape		
Feet / Legs	4 adjustable feet		
Castors	4 rollers		
Exterior Finish	Black		
Interior Finish	Black RAL9005		
Interior Light	LED		
Lock	Yes		

Measures and Content				
Temperature Range	°C	+2 to +10		
Climate Class		4		
Gross / Net Weight	kg	166 / 153		
Gross / Net Volume	I	707 / 535		

Cooling and Functions	
Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic
Refrigerant	R290
Refrigerant Charge g	115
Thermometer	Yes

Power and Consumption				
Energy Class		С		
Energy Consumption	kWh/24h	2.63		
Annual Energy Cons.	kWh/year	960		
Input Power	W	410		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	48		

Dimensions		
Internal Dimension (WxDxH)	mm	810 x 561 x 1556
External Dimension (WxDxH)	mm	890 x 740 x 1990
Packed Dimension (WxDxH)	mm	950 x 840 x 2160
40ft Container Load	pcs	28