



PDC126 VS SL LED

Black impulse cooler

Product Features

- Energy saving variable speed compressor
- Plexi glass sides for great product visibility
- Impressive storage space
- Tilting function for better product display
- LED interior light
- 4 solid castors, 2 with brakes
- Bumper bars on 4 sides
- Maintenance free condenser



Sliding glass lids



LED light

Energy efficient impulse cooler with glass lids

The PDC impulse cooler is all about showcasing the products inside. It has clear plexi glass on all four sides as well as easy sliding glass lids on the top. Furthermore, it comes with two horizontal LED light strips. This provides a fantastic product visibility no matter from which direction the customer sees it. If the cooler is placed against a wall, it can be tilted 15 degrees for a better product display.

The island cooler has a variable speed compressor as well as highly efficient EC fans, allowing for a more silent and energy efficient operation. This is a unique feature for this kind of product.

The unit is easy to move with tubular 360 degree bumper bars as well as strong casters with brakes. That way you can always relocate it to wherever the need is biggest in your store. In terms of maintenance, the impulse cooler has a maintenance free condenser as well as a stainless steel bottom plate to ensure easy cleaning.

Design and Material		
Lid No & Type	2 curved sliding glass lids	
Castors	4 wheels, 2 with brake	
Exterior Finish	Black / Glass	
Interior Finish	Stainless steel / Glass	
Interior Light	2 x Vertically LED	
Lock	No	

Measures and Content				
Total Display Area	m²	1.51		
Temperature Range	°C	-1 to +5		
Climate Class		3		
Gross / Net Weight	kg	176 / 133		
Gross / Net Volume	I	408 / 190		

Cooling and Functions				
Type of Controller		Electronic		
Type of Cooling		Ventilated		
Type of Defrost		Automatic-Off Cycle		
Refrigerant		R290		
Refrigerant Charge	g	150		
Thermometer		Yes		

Power and Consumption						
Energy Class		D				
Energy Consumption	kWh/	24h 5.25				
Annual Energy Cons.	kWh/	year 1916				
Max Ambient		25°C at 60% RH				
Input Power	W	700				
Voltage / Frequency	V/Hz	220-240/50				
Noise Level	dB(A)	52				
Dimensions						
Internal Dimension (WxDxH)	mm	1210 x 1080 x 342				
External Dimension (WxDxH)	mm	1405 x 1210 x 1005				
Packed Dimension (WxDxH)	mm	1335 x 1170 x 1140				
40ft Container Load	pcs	36				